



Water-Data Report 2011

**280503082143702 Local number ROMP 68 SUWANNEE WELL NEAR ANTIOCH FL**

Floridan aquifer system  
Suwannee Limestone

Hillsborough County, FL

LOCATION.--Lat 28°05'02.2", long 82°14'34.8" referenced to North American Datum of 1983, in SE ¼ SW ¼ SE ¼ sec.31, T.27 S., R.21 E., Hillsborough County, FL, Hydrologic Unit 03100205.

**GROUNDWATER RECORDS**

WELL CHARACTERISTICS.--Depth 221 ft. Upper casing diameter 7.0 in; top of first opening 120 ft, bottom of last opening 221 ft.

DATUM.--Land-surface datum is 56 ft above National Geodetic Vertical Datum of 1929. Measuring point: Shelter floor, 3.51 ft above land-surface datum, May 2002 to present.

PERIOD OF RECORD.--August 1981 to September 1989; October 1989 to September 1990 (miscellaneous water level measurements); October 1991 to September 1992; October 1992 to September 2011 (miscellaneous water level measurements), discontinued. Prior to October 1990, published as ROMP 68-2 Suwannee Well near Antioch.

GAGE.--Miscellaneous measurement with chalked tape.

EXTREMES FOR PERIOD OF RECORD.--Highest daily maximum water level, 51.58 ft NGVD, Sep. 6, 1985; lowest measured, 39.14 ft NGVD, May 18, 2009.

**WATER SURFACE ELEVATION IN FEET NGVD 1929  
WATER YEAR OCTOBER 2010 TO SEPTEMBER 2011**

[Measurement method: S, steel tape. Water-level status: - - , static.]

Date	Water level	Measure-ment method	Water-level status	Date	Water level	Measure-ment method	Water-level status
May 23	44.68	S	--	Sep 13	47.62	S	--

Water year 2011 lowest: 44.68, May 23, 2011, highest: 47.62, Sep 13, 2011